



VALKYRIE C IP65

CONVENTIONAL WALL MOUNT
SOUNDER/ BEACON OUTDOOR USE-IP65



The VALKYRIE CS IP65 is a wall mounted Conventional Sounder/ Beacon with low power consumption. It is specifically designed to be used outdoors. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	20V to 30V DC
CURRENT - SOUNDER/BEACON ACTIVE	10 mA - 280 mW @ 28V DC
MAXIMUM SOUNDER OUTPUT	95,3 dB (@ 1 meter - 30V DC)
RESET/START-UP TIMES	20 seconds max.
PROTECTION CATEGORY	Type B - Outdoor Use
CABLE SIZE	0.5-2.5 mm ²
COLOUR	Red
CASE MATERIAL	ABS and PC - Flame Retardant rating UL 94 V2
OPER. TEMPERATURE	-25°C to 70°C
MAX. HUMIDITY	95% RH Non-Condensing
DIMENSIONS	112 (D) x 110 (H) mm included base
WEIGHT	315g included base and 350g inc. packaging

For EN54-13 compliance, please check the control panel manual specifications.

ORDER CODE

VALKYRIE CS IP65	CONVENTIONAL WALL SOUNDER - IP65 RATED	1328-CPR-0300 0359-UKCA-CPR-00198
VALKYRIE CSB IP65	CONVENTIONAL WALL SOUNDER/ BEACON - IP65 RATED	1328-CPR-0300 0359-UKCA-CPR-00198



© 231130

Global Fire Equipment SA

Parque Industrial Municipal da Barracha, 8150-016 São Brás de Alportel - PORTUGAL

Telephone: (00351) 289 896 560 / Email: info@globalfire-equipment.com / Web: www.globalfire-equipment.com

