



VULCAN 2 VOX C

CONVENTIONAL VOICE SOUNDER

The **VULCAN 2 VOX C** is a wall mounted Conventional Voice Sounder which is available in either White or Red housings. The VULCAN 2 VOX C, can broadcast up to 2 differentiated pre-loaded messages: Fire and Alert. The desired messages can be downloaded from our own proprietary recording PC application, via a standard USB interface.

KEY FEATURES

- Multi-Message. Follows Panel's Sounder Programming
- Multi-Language
- 92 dBA maximum output
- Messages easily programmed via USB interface using dedicated software
- Synchronisation for fast activation
- Compatible with most conventional panels

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	20V to 30V DC
SUPPLY CURRENT - SOUNDER ACTIVE	28mA (Average) - 65mA (Peak) @24V DC
SOUNDER OUTPUT @ 1 METER	Tone 88dBA - Voice Message 92dBA
TOTAL AUDIO MEMORY SIZE	4 minutes (decoded audio) up to 16 minutes (encoded audio)
MAX. CABLE SIZE	2.5mm ²
PROTECTION	IP21C - Type A - Indoor use
COLOUR	Red or White
CASE MATERIAL	ABS and PC
OPERATING TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
DIMENSIONS	100 (D) x 29 (H) mm base included
WEIGHT	127g - 149g Lid included

ORDER CODE

VULCAN 2 VOX CS	CONVENTIONAL VOICE BASE SOUNDER
VULCAN 2 VOX CSB	CONVENTIONAL VOICE BASE SOUNDER WITH BEACON